

# Introducing the Yaesu FT-950 transceiver for DX enthusiasts

## Superb receiver performance

## Direct lineage from the legendary FT DX 9000 and FT-2000



### HF/50 MHz 100 W Transceiver

## FT-950

- Triple-conversion super-heterodyne receiver architecture, using 69.450 MHz 1st IF
- Eight narrow, band-pass filters in the RF stage eliminate out of band interference and protect the powerful 1st IF
- Factory installed selectable 1st IF 3, 6, & 15 kHz Roofing Filters
- High-speed Direct Digital Synthesizer (DDS) and high-spec Digital PLL for outstanding Local Oscillator performance
- Advanced Multi-function 30 kHz 32-bit Floating Point IF DSP IF WIDTH, IF SHIFT, NOTCH, and CONTOUR Features
- DSP enhancement of Transmit SSB/AM signal quality with Parametric Microphone Equalizer and Speech Processor
- Built-in high stability TCXO ( $\pm 0.5$  ppm after 1 minute @ 77 ° F / +25 ° C)
- Built-in automatic antenna tuner ATU, with 100 memories
- Powerful CW operating capabilities for CW enthusiasts
- Five Voice Message memories, with the optional DVS-6 unit
- Large Multi-color VFD (Vacuum Fluorescent Display)
- Optional Data Management Unit (DMU-2000) permits display of various operating conditions, transceiver status and station logging.
- Optional RF  $\mu$ -Tune Units for 160 m, 80/40 m and 30/20 m Bands

#### Optional, YAESU Exclusive, Fully-Automatic $\mu$ -Tuning Preselector System!

Fully automatic, Ultra-sharp, External  $\mu$ -Tuning Preselector (optional) features a 1.1" (28 mm) Coil for High Q



#### Optional External Data Management Unit (DMU-2000) Provides Many Display Capabilities



Shown with after-market keyer paddle, keyboard, and monitor (not supplied). DMU-2000 Data Management Unit (option)